



FBC Chemical Corp.
Asphalt Products Division

P.O. Box 599
634 Route 228
Mars, PA 16046
(724) 625-3116

Acrylic Roof Primer (Solvent-Based)

Item Number: 81050

DESCRIPTION: Acrylic Roof Primer is a clear, fast drying, solvent based primer that provides excellent adhesion to most surfaces. It will provide an excellent base to insure adhesion over oily, weathered asphalt, built-up and metal roofs. Acrylic Roof Primer provides a unique combination of hardness and flexibility without tracking at elevated temperatures. The resultant film will accommodate roof flexing while tying up loose dust.

USES: Acrylic Roof Primer should be used as a primer prior to applying Storm Seal Elastomeric Roof Coating. When applied over metal, weathered asphalt, dusty or oily substrates, it dries quickly to provide a tack free base coat.

Caution: This product is **not** intended for use over coal tar, new asphalt roofs which have weathered less than 90 days, vinyl or rubber substrates.

PREPARATION: Surfaces to be coated should be power washed or swept to remove as much dirt, dust, rust and grease or oil as possible. Allow surfaces to dry prior to application.

NOTE: The use of Acrylic Roof Primer is not a substitute for proper cleaning of roof surfaces prior to top-coating.

APPLICATION: Acrylic Roof Primer may be brushed rolled or sprayed. Its low viscosity allows the use of a typical garden sprayer to ease application. Apply in a thin uniform film at a rate of $\frac{1}{2}$ - $\frac{3}{4}$ gallon per 100 square feet. The dried film should be top-coated within 21 days of application. If top-coating is delayed over 21 days or in extremely dusty conditions, it is recommended that the primer be re-applied prior to top-coating.

COVERAGE RATE: 1/3 to 1/2 gallon per 100 square feet.

PACKAGING: 55-gallon drum, 5-gallon pail

CLEAN UP: Tools may be cleaned with Xylene or Mineral Spirits. Use caution when handling any hazardous material.

CAUTION: Use only with adequate ventilation. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF THE REACH OF CHILDREN.** Keep container covered when not in use. See MSDS for further information.