



FBC Chemical Corp.
Asphalt Products Division
P.O. Box 599
634 Route 228
Mars, PA 16046
(724) 625-3116

ASPHALT FOUNDATION TROWEL-ON MASTIC

Item Number: 82650

USE: For waterproofing outside cement block, concrete or brick foundations.

PRODUCT DESCRIPTION: A protective coating made with an asphalt base.

APPLICATION: Use stiff brush or broom to remove dust, dirt and debris. Allow green concrete to cure thoroughly. Apply with trowel at rate of 4 gallons per 100 square feet.

CAUTION: Allow mastic to thoroughly dry 2-3 days; then when back filling, be Careful to prevent sharp rocks, stones, etc. from piercing coating.

SPECIFICATIONS: Meets Performance Requirements of Federal Specification SS-C-153B, Type 1. Meets ASTM D 4586 (Type 1).

Color..... Black – Dark Brown
Total Solids Content..... 72%
Solvent Content..... 28%
Solvent Type..... Mineral Spirits, Rule 66 or Equiv.
Flash Point (T.C.C.)..... 105 F
Weight per gallon @ 60 F..... 9-9.5#
Base Asphalt
 Softening Point (B&R)..... 125-145F
 Penetration 77 F
 5 sec., 100 grs..... 30-60

PACKAGING: 55-gallon drums and 5-gallon pails

SHIPPING WEIGHTS: 55 gallons = 465#, 5 Gallons = 43#