



**FBC Chemical Corp.**  
**Asphalt Products Division**

P.O. Box 599  
634 Route 228  
Mars, PA 16046  
(724) 625-3116

**XL-2 CRACKFILLER (Pour Grade)**

Item Number: 87600

**DESCRIPTION:** XL-2 Crackfiller is a latex modified asphalt emulsion sealant designed to fill cracks in asphalt or concrete horizontal surfaces. It blends with blacktop surfaces to prevent water seepage and the damage it can cause. This dramatically increases the life of the pavement. Product #8760 is supplied in easy-to-use gallon bottles with pour spouts. XL-2 Crackfiller may be top coated with either asphalt or coal tar driveway sealers.

**USES:** Fills cracks in asphalt & concrete joints, driveways and parking areas up to ½ inch in width.

**PREPARATION & APPLICATION:**

1. Broom or hose down area thoroughly to remove loose dust, dirt and debris.
2. Remove any standing water.
3. Shake container well.
4. Remove container top and invert the attached pour spout. Replace cap with the pour spout extended.
5. Snip off approximately 1/8" of spout and direct the flow into the crack. Hand pressure on the container will allow the material to flow evenly.
6. For cracks deeper than ½", apply in 2 coats allowing 12-24 hours between application. This will reduce tracking.
7. If the surface is to be used prior to complete curing, fill cracks to ¼" from the top of the surface and lightly cover with sand. This will help eliminate tracking.

**COVERAGE RATE:** 75-80 lineal feet for a ½" X ½" crack. Coverage rates will vary based on the size of the crack.

**CLEAN UP:** Soap & water may be used to clean this material prior to drying. Dried material may be cleaned with Mineral Spirits. Use caution when handling any hazardous cleaning compound or solvent.

**CAUTION:** Keep away from heat, sparks and flame. May cause eye and skin irritation. Avoid prolonged contact with skin. Wash exposed areas with soap and water. **Do not take internally and keep out of the reach of children.** If swallowed, contact physician immediately.

**STORAGE: PROTECT FROM FREEZING!**

**PACKAGING:** 6-1 gallon/carton, 28 cartons/pallet (168 gallons)